




SPECIFICATION SHEET

SPECIFICATION SHEET NO.	R0725- TTR6MFTTF00S6A	
DATE	Jul. 25, 2024	
REVISION	A1	Updated With Most Recent Data
DESCRIPTION AND MAIN PARAMETRICS	<p>SMD Glass Passivated Bridge Rectifier, TTR Series, Case TTF Type, Reverse Voltage 1000V Max. Forward Current 6.0 A Max..</p> <p>Operating Temp. Range -55°C ~+150°C</p> <p>Package in Tape/Reel, 3000pcs/Reel</p> <p>RoHS III/REACH Compliant and Halogen Free (HF)</p>	
CUSTOMER		
CUSTOMER PART NO.		
CROSS REF. PART NO.		
ORIGINAL MFG/PART NO.	MDD Diodes/TTR6MF	
PART CODE	TTR6MFTTF00S6A	

VENDOR APPROVE			
Issued/Checked/Approved			
DATE: Jul. 25, 2024			

CUSTOMER APPROVE	
DATE:	

SMD GLASS PASSIVATED BRIDGE RECTIFIER TTR SERIES CASE TTF

MAIN FEATURE

- Glass Passivated Chip Junction
- Reverse Voltage - 1000 V
- Forward Current- 6.0 A
- REACH/RoHS III Complaint and Halogen Free
- Fast Reverse Recovery Time



- **APPLICATION**

- Designed for Surface Mount Application

- **ELECTRICAL CHARACTERISTICS**

- See Page 4~ Page 5

HOW TO ORDER

- Please Follow Up Part Code Guide And Indicate Pat Code When You Order Or RFQ For Custom Specification

PART CODE GUIDE

RFQ
Request For Quotation

CODE	NAME	KEY SPECIFICATION OPTION
TTR	Product Series Code	SMD Glass Passivated Bridge Rectifiers, TTR Series
6MF	Specification Code	For Voltage Range - 1000 V, Current - 6.0 A
TTF	Case Code	Case TTF
00S	Internal Control Code	Custom letter A~Z, a-z or Digits (0-9)
6A	Marking Code	Custom letter A~Z, a-z or Digits (0-9) for Marking "6A"

SMD GLASS PASSIVATED BRIDGE RECTIFIER TTR SERIES CASE TTF

DIMENSION (Unit: Inch/mm)





Image for reference




Marking:

6A

Case TTF



Recommend Pad Layout



SMD GLASS PASSIVATED BRIDGE RECTIFIER TTR SERIES CASE TTF
MECHANICAL DATA

Case	Terminals	Polarity	Mounting Position	Weight per piece
JEDEC Case TTF Molded plastic body	Solderable per MIL-STD-750, Method 2026	Polarity symbol Marking on body	Any	0.0163 ounce, 0.461 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS - @ 25 °C

PARAMETER	SYMBOLS	VALUE	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	1000	V
Maximum RMS Voltage	V_{RMS}	700	V
Maximum DC Blocking Voltage	V_{DC}	1000	V
Average Rectified Output Current at $T_c = 100^\circ\text{C}$	I_o	6.0	A
Peak Forward Surge Current, 8.3ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	200	A
Rating for Fusing	I^2t	166	A^2S
Typical Thermal Resistance (Note 2)	$R_{\theta JA}$	60	$^\circ\text{C}/\text{W}$
	$R_{\theta JC}$	6	
	$R_{\theta JL}$	14	
Operating and Storage Temperature Range	T_j, T_{stg}	-55 ~ +150	$^\circ\text{C}$

Note:

1. Single Phase Half-wave 60hz, resistive Or Inductive Load, For Capacitive Load Current Derate By 20% .
2. Measured At 1mhz And Applied Reverse Voltage Of 4 V D.C.
3. P.C.B. Mounted With $4 \times 1.5'' \times 1.5''$ (3.81×3.81 Cm) copper Pad Areas.

SMD GLASS PASSIVATED BRIDGE RECTIFIER TTR SERIES CASE TTF
MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS- @ 25 °C

PARAMETER	SYMBOL	TEST CONDITIONS	VALUE			UNITS
			Min.	Typ.	Max.	
Instantaneous Forward Voltage	V_F	$I_F = 6A$ $T_J = 25^\circ C$	-	-	1.0	V
Reverse Current At DC Blocking Voltage	I_R	$T_J = 25^\circ C$	-	-	5.0	μA
		$T_J = 125^\circ C$	-	-	200	
Maximum Reverse Recovery Time	t_{rr}	Measured with $I_F = 0.5 A$, $I_R = 1 A$, $I = 0.25 A$	-	-	500	ns
Typical Junction Capacitance	C_j	$f = 1MHz$, $V_R = 4V$ DC $T_J = 25^\circ C$	-	80	-	pF

SMD GLASS PASSIVATED BRIDGE RECTIFIER TTR SERIES CASE TTF

TYPICAL CHARACTERISTIC CURVES - For Reference Only

Fig.1 Average Rectified Output Current Derating Curve





Fig.2 Typical Reverse Characteristics



SMD GLASS PASSIVATED BRIDGE RECTIFIER TTR SERIES CASE TTF

TYPICAL CHARACTERISTIC CURVES - For Reference Only

Fig.3 Typical Instantaneous Forward Characteristics





Fig.4 Typical Junction Capacitance



SMD GLASS PASSIVATED BRIDGE RECTIFIER TTR SERIES CASE TTF

TYPICAL CHARACTERISTIC CURVES - For Reference Only

Fig.5 Maximum Non-Repetitive Peak Forward Surge Current





Fig.6- Typical Transient Thermal Impedance




SMD GLASS PASSIVATED BRIDGE RECTIFIER TTR SERIES CASE TTF
RELIABILITY

NUMBER	EXPERIMENT ITEMS	EXPERIMENT METHOD AND CONDITIONS	REFERENCE DOCUMENTS
1	Solder Resistance Test	Test 260°C± 5°C for 10 ± 2 sec. Immerse body into solder 1/16" ± 1/32"	MIL-STD-750D METHOD-2031.2
2	Solderability Test	230°C ±5°C for 5 sec.	MIL-STD-750D METHOD-2026.1 0
3	Pull Test	1 kg in axial lead direction for 10 sec.	MIL-STD-750D METHOD-2036.4
4	Bend Test	0.5Kg Weight Applied To Each Lead, Bending Arcs 90 °C ± 5 °C For 3 Times	MIL-STD-750D METHOD-2036.4
5	High Temperature Reverse Bias Test	TA=100°C for 1000 Hours at VR=80% Rated VR	MIL-STD-750D METHOD-1038.4
6	Forward Operation Life Test	TA=25°C Rated Average Rectified Current	MIL-STD-750D METHOD-1027.3
7	Intermittent Operation Life Test	On state: 5 min with rated IRMS Power Off state: 5 min with Cool Forced Air. On and off for 1000 cycles.	MIL-STD-750D METHOD-1036.3
8	Pressure Cooker Test	15 PSIG, TA=121°C, 4 hours	MIL-S-19500 APPENOIXC
9	Temperature Cycling Test	-55°C~+125°C; 30 Minutes For Dwelled Time 5 minutes for transferred time. Total: 10 cycles.	MIL-STD-750D METHOD-1051.7
10	Thermal Shock Test	0°C for 5 minutes., 100°C for 5minutes, Total: 10 cycles	MIL-STD-750D METHOD-1056.7
11	Forward Surge Test	8.3ms Single Sale Sine-wave One Surge.	MIL-STD-750D METHOD-4066.4
12	Humidity Test	TA=65°C, RH=98% for 1000 hours.	MIL-STD-750D METHOD-1021.3
13	High Temperature Storage life Test	150°C for 1000 Hours	MIL-STD-750D METHOD-1031.5

SMD GLASS PASSIVATED BRIDGE RECTIFIER TTR SERIES CASE TTF

SUGGESTED REFLOW PROFILE - For Reference Only



PROFILE FEATURE		PB-FREE ASSEMBLY
Average Ramp-up Rate (Ts Max to Tp)		3°C/second Max
Preheat	Temperature Min (Ts Min.)	150°C
	Temperature Max (Ts Max.)	200°C
	Time (ts Min. to ts Max.)	60~120 seconds
Time maintained above	Temperature (Tl)	217°C
	Time (tl)	60~150 seconds
Peak/Classification Temperature (Tp)		260 +/-5°C
Time within 5°C of actual Peak Temperature (tp)		20~40 seconds
Ramp-down rate		6 °C /Second Max.
Time 25 °C to Peak Temperature		8 minutes Max.
Suggest reflow times		3 Times Max.

SMD GLASS PASSIVATED BRIDGE RECTIFIER TTR SERIES CASE TTF

IMPORTANT NOTES AND DISCLAIMER

1. **ROHS COMPLIANCE:** The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU RoHS Directive (EU) 2015/863 EC (RoHS3). RoHS Test Report for this product can be obtained at Download Center.
2. **REACH COMPLIANCE:** REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, REACH Test Report for this product can be obtained at Download Center.
3. All Product parametric performance is indicated in the Electrical Characteristics for the listed herein test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.
4. NextGen Component, Inc (*NextGen*) reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
5. *NextGen* makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, not does *NextGen* assume any liability for application assistance or customer product design.
6. *NextGen* does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application. No license is granted by implication or otherwise under any intellectual property rights of NextGen.
7. *NextGen* products are not authorized for use as critical components in life support devices or systems without express written approval by *NextGen*.
8. *NextGen* requires that customers first obtain an RMA (Returned Merchandise Authorization) number prior to returning any products. Returns must be made within 30 days of the date of invoice, be in the original packaging, unused and like-new condition. At the time of quoting or purchasing, a product may say that it is Non-Cancelable/ Non-Returnable (NCNR). These products are not returnable and not refundable.