




| | | |
|---|---|-------------------------------|
| SPECIFICATION SHEET NO. | R1010- FB450K0000L115 | |
| ORIGINAL MFG/PART NO | TGS Crystals/CF 450KFW BLH/LTW450KFx | |
| DATE | Oct. 10, 2024 | |
| REVISION | A4 | Updated With Most Recent Data |
| DESCRIPTION AND MAIN PARAMETRICS | <p>KHz DIP Ceramic Filter, GDT Type, 5 Pins, FB Series</p> <p>Case 11070, Dimension L11.0*W7.0*H8.0mm</p> <p>450KHz, Insertion Loss. 8.0dB Max.; 6dB Bandwidth: ±6.0KHz Min.</p> <p>Group Delay Time (GDT) Ripple Deviation: 40µSec. Max. within f0 ±4.5KHz</p> <p>Input/Output Impedance: 2000 ohm,</p> <p>Operating Temp. Range -20°C ~+85°C, Package in Bulk</p> <p>REACH/RoHS/RoHS III Compliant, RoHS Annex III lead Exemption (Exempt per RoHS EU 2015/863)</p> | |
| CUSTOMER | | |
| CUSTOMER PART NUMBER | | |
| CROSS REF. PART NUMBER | | |
| MEMO | | |

| | | | |
|-------------------------|---|--|---|
| VENDOR APPROVE | | | |
| Issued/Checked/Approved |  |  |  |
| Date: Oct. 10, 2024 | | | |

| |
|-------------------------|
| CUSTOMER APPROVE |
| |
| Date: |

MAIN FEATURE

- KHz DIP Ceramic Filter, GDT Type, 5 Pins, Case 1170
- Black case, Dimension L11.0*W7.0*H8.0mm
- Low Cost And Short Shipment
- Group Delay Time (GDT) Ripple Deviation: 40μSec. Max. within f0 ±4.5KHz
- Reflow Profile Condition 260 °C Max.
- Cross Main Competitors Parts CFWL series
- REACH/RoHS/RoHS III compliant, RoHS Annex III lead Exemption
(Exempt per RoHS EU 2015/863)



Image shown is a representation only. Exact specifications should be obtained from the product dimension.



APPLICATION

- Communication Electronics

HOW TO ORDER

- Please follow up part code guide and indicate part code when you order or RFQ.

PART CODE GUIDE

RFQ
[Request For Quotation](#)


| CODE | NAME | KEY SPECIFICATION OPTION |
|------|--------------------|--|
| FB | Product Series | KHz DIP Ceramic Filter, 5 Pins, Case 11070 Dimension L11.0*W7.0*H8.0mm |
| 450K | Frequency Range | 450: 450KHz; 455K: 455KHz |
| 0000 | Internal Control | Letter or Digits (A~Z, a~z or 1~9) |
| L | DIP Type Package | Package in bulk |
| 115 | Special Parametric | Letter or Digits (A~Z, a~z or 1~9) |
| - XX | Suffix | Blank: N/A XX: Internal Control Code, Letter A~Z, a~z or digits (0~9) for Special/Custom Parameters |

DIMENSION (Unit: mm)

Case 11070, 5 Pins

L11.0*W7.0*H8.0mm


Top View




Marking

Line 1: CF or LTW
 Line 2: Frequency Range
 + Internal Code

Side View



Bottom View




Connection

- 1: Pin 1: Input
- 2: Pin 2: Ground
- 3: Pin 3, Ground
- 4: Pin 4: Ground
- 5: Pin 5: Output

MEASUREMENT

- Measurement shall be carried out at the standard temperature of $25\pm 2^{\circ}\text{C}$. If no specific requirements, Test can be carried out under $5-35^{\circ}\text{C}$.
- Measuring Circuit



$R_g + R_1 = R_2 = \text{Output/input Impedance}$

GENERAL ELECTRICAL PARAMETERS

| PARAMETER | UNITS | VALUE | | | CONDITION |
|-----------------------|--------------------|-------|---------|-----------|--|
| | | MIN. | TYPICAL | MAX. | |
| Operation Temperature | $^{\circ}\text{C}$ | -20 | | +85 | |
| Storage Temperature | $^{\circ}\text{C}$ | -40 | | +85 | |
| Temperature Stability | % | | | ± 0.5 | @ $-20^{\circ}\text{C} \sim +85^{\circ}\text{C}$ |
| Stop Band Attenuation | dB | 40 | | | @ $f_0 \pm 100\text{KHz}$ |
| Ripple | dB | | | 1.0 | @ $f_0 \pm 3\text{KHz} \sim 10\text{KHz}$ |
| Spurious Response | dB | 20 | | | @ $0.1 \sim 1.0\text{MHz}$ |
| Insulation Resistance | $\text{M}\Omega$ | 100 | | | @ DC 25V 1 minute |

ELECTRONICAL RIPPLE PARAMETERS – FOR DIFFERENT PART CODE

| Part Code | Center Freq. (KHz) | Min. Bandwidth | | | Max. Insertion Loss @Min. loss point | Max. GDT Ripple Deviation | Input/ Output Impedance |
|-----------------------|--------------------|----------------|-------|--------|--------------------------------------|---------------------------|-------------------------|
| | | @3 dB | @6 dB | @50 dB | | | |
| | | KHz | | | | | |
| FB450K0000L111 | 450±1.5 | ±12.0 | ±15.0 | ±30.0 | 5.0 | 30 (within f0±10KHz) | 1500 |
| FB450K0000L112 | 450±1.5 | ±10.0 | ±12.5 | ±27.5 | 6.0 | 30 (within f0±10KHz) | 1500 |
| FB450K0000L113 | 450±1.0 | ±8.0 | ±10.0 | ±25.0 | 7.0 | 30 (within f0±7KHz) | 1500 |
| FB450K0000L114 | 450±1.0 | ±5.0 | ±7.50 | ±20.0 | 8.0 | 30 (within f0±5KHz) | 1500 |
| FB450K0000L115 | 450±1.0 | ±4.5 | ±6.0 | ±17.5 | 8.0 | 40 (within f0±4.5KHz) | 2000 |
| FB450K0000L116 | 450±1.0 | ±3.0 | ±4.5 | ±15.0 | 9.0 | 40 (within f0±3KHz) | 2000 |
| FB450K0000L115 | 455±1.5 | ±12.0 | ±15.0 | ±30.0 | 5.0 | 30 (within f0±10KHz) | 1500 |
| FB455K0000L112 | 455±1.5 | ±10.0 | ±12.5 | ±27.5 | 6.0 | 30 (within f0±10KHz) | 1500 |
| FB455K0000L113 | 455±1.0 | ±8.0 | ±10.0 | ±25.0 | 7.0 | 30 (within f0±7KHz) | 1500 |
| FB455K000LG114 | 455±1.0 | ±5.0 | ±7.50 | ±20.0 | 8.0 | 30 (within f0±5KHz) | 1500 |
| FB455K0000L115 | 455±1.0 | ±4.5 | ±6.0 | ±17.5 | 8.0 | 40 (within f0±4.5KHz) | 2000 |
| FB455K0000L116 | 455±1.0 | ±3.0 | ±4.5 | ±15.0 | 9.0 | 40 (within f0±3KHz) | 2000 |

Note

- Center Frequency f0 is @Center of 6dB Bandwidth.
- Specification is subject to changed without notice, please contact us for any update
- The Parameters in the above table are all general specifications. If you need other Parameters, please contact us.

PHYSICAL CHARACTERISTICS

| TEST ITEMS | MEASUREMENT CONDITION | REQUIREMENT |
|------------------------|---|---|
| Random Drop | Filter shall be measured after 3 times random drops from the height of 30cm on concrete floor | No visible damage and it meet Table at Page 4~5 |
| Vibration | Filter shall be measured after being applied vibration of amplitude of 1.5mm with 10-55Hz band of vibration frequency to each of 3 perpendicular directions for 2 hours | No damage and it meet Table at Page 4~5 |
| Solderability | Lead terminals are immersed in aide solder for 5 sec and then immersed in soldering bath of 230±5°C, for 3±0.5 sec. | At least 95% lead terminals shall be covered with solder. |
| Substrate Bending Test | Apply pressure in the direction of arrow at a rate of about 0.5mm per second until it reaches a bend of 3mm and hold for 30s. | No damage, no cut-off and it meet Table at Page 4~5 |
| Adhesion | A static load of 20N to the direction of the arrow shall be applied on the core of the component and hold for 10 seconds. Filter shall be soldered correctly and tightly to PCB. | No damage, no cut-off and it meet Table at Page 4~5 |
| Reflow Soldering | Put on the solder paste on the printed wiring board the samples shall be mounted and soldered under the condition, then it shall be subjected to the room atmosphere for 24 hours prior to the measurement. | No damage, no cut-off and it meet Table at Page 4~5 |

ENVIRONMENTAL CHARACTERISTICS

| TEST ITEMS | MEASUREMENT CONDITION | REQUIREMENT |
|---------------------------|---|---------------------------------|
| Humidity | After being placed in a chamber with 90-95% R.H. at 40±2°C for 100 hours and then being placed in room temperature for 1 hour, filter shall be measured. | It shall meet Table at Page 4~5 |
| Resistance to Solder Heat | After being placed in a chamber with 80±2°C, for 100 hours and then being placed in room temperature for 1 hour, filter shall be measured. | It shall meet Table at Page 4~5 |
| High Temperature | After being placed in a chamber with 80±2°C, for 100 hours and then being placed in room temperature for 1 hour, filter shall be measured. | It shall meet Table at Page 4~5 |
| Low Temperature | After being placed in a chamber with -20±2°C, for 100 hours and then being placed in room temperature for 1 hour, filter shall be measured. | It shall meet Table at Page 4~5 |
| Heat Shock | After being kept at room temperature, filter shall be placed at temperature of -55 °C, for 30 minutes, then be placed at temperature. 85°C, for 30 minutes. After that returned to -55°C again. Repeated above cycle for 5 times. After being kept in room temp. for 1 hour, filter shall be measured | It shall meet Table at Page 4~5 |

IMPORTANT NOTES AND DISCLAIMER

1. **ROHS COMPLIANCE:** The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU RoHS Directive (EU) 2015/863 EC (RoHS3). RoHS Test Report for this product can be obtained at Download Center.
2. **REACH COMPLIANCE:** REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, REACH Test Report for this product can be obtained at Download Center.
3. All Product parametric performance is indicated in the Electrical Characteristics for the listed herein test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.
4. NextGen Component, Inc (*NextGen*) reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
5. *NextGen* makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, not does *NextGen* assume any liability for application assistance or customer product design.
6. *NextGen* does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application. No license is granted by implication or otherwise under any intellectual property rights of NextGen.
7. *NextGen* products are not authorized for use as critical components in life support devices or systems without express written approval by *NextGen*.
8. *NextGen* requires that customers first obtain an RMA (Returned Merchandise Authorization) number prior to returning any products. Returns must be made within 30 days of the date of invoice, be in the original packaging, unused and like-new condition. At the time of quoting or purchasing, a product may say that it is Non-Cancelable/ Non-Returnable (NCNR). These products are not returnable and not refundable.