



Image shown is a representation only. Exact specifications should be obtained from the product dimension

PRODUCT NAME:	Connector Base Side Entry 3A IP65
REVISION:	A3
NEXTGEN ORDER PART CODE*:	H3ABK1LW00L001
CROSS REF. PART NO.:	09200030301
ORIGINAL MFG PART CODE:	H3A-BK-1L/W
ORIGINAL MFG PART NO.:	1100033241001
ORIGINAL MANUFACTURER:	Wain Electrical/Wain Connectors

*: Please Indicate this Part Code For RFQ/Order Support

WAIN
CONNECTORS



AUTHORIZED DISTRIBUTOR





NextGen Components, Inc.

US Warehouse Location: 9 Orchard Road, Suit 106, Lake Forest, CA 92630, USA

RFQ/Order Support: sales@NextGenComponent.com

Note: This coversheet was created by NextGen Components, Inc. ("NextGen"). The attached last document was created by the part manufacturer, not NextGen, and is provided strictly 'as is.' NextGen, its subsidiaries, affiliates, employees, and agents make no representations or warranties regarding the attached last document and disclaim any liability for the consequences of relying on the information therein. All referenced brands, product names, service names, and trademarks are the property of their respective owners.

DIMENSION – Unit: mm



Panel cut out

GENERAL PRODUCT ATTRIBUTES & TECHNICAL CHARACTERISTICS

ATTRIBUTE		DESCRIPTION
Product Category		Connectors, Interconnects/Heavy Duty Connectors Bases
Product Name		Connector Base Side Entry 3A IP65
Part Category No.		110003
Series Category No.		H3A
Specification		3A
Housing Type		Unsealed cove
Outgoing Method		Bottom Outlet
Locking Type		Single Lock
Housing Material		Die Casting Zinc
Housing Color		RAL 7037 (Field Gray)
Surface Treatment		Powder Coating
Interlocking Method		Metal Elastic Connection
Material		Galvanized Iron
Seals		NBR
Flame Retardant Rating As Per UL94		V0
Working Temperature		-40 °C~+ 125 °C
Protection Rating		IP65 (acc. to IEC 60529 for coupled connector)
Locking Element	Locking Type	Single Locking Latch
	Material	Steel Lever With Zinc Plated
Cable Entry		Bottom Entry
Need Crimp Contacts Separately		No

PRODUCTS CERTIFICATIONS

APPROVALS	AUTHENTICATION
UL	
CUL	

ENVIRONMENTAL & EXPORT CLASSIFICATIONS

ATTRIBUTE	DESCRIPTION
RoHS Status	ROHS3 Compliant With Exemption
Moisture Sensitivity Level (MSL)	1 (Unlimited)
REACH Status	REACH Unaffected
ECCN	EAR99
HTSUS	8538.90.8180

